

Configurations FM4-LO



Mechatronik

Picture	Art.-No.	Description	Basic	Standard	Edge
	785539:005.26	Contact wire measuring device FM4-LO Measurement of the height and stagger of contact wires by vertical laser beam and crosshair optics	X	X	-
	785539:010.26	Contact wire measuring device FM4-LO-MVK Measurement of the height and stagger of contact wires by vertical laser beam and crosshair optics, incl. mirror attachment for laser beam deflection to measure the distance between pole leading edge – track center	-	-	X
	785539:005.26.BA-E	Instruction manual FM4-LO Language English	X	X	X
	99.53717	Aluminum transport case for FM4-LO For the transport of the measuring device, accessories and documents	X	X	X
	785532:051.26	Measuring bar standard Adjusted to track gauge: 1435 mm or to another track gauge in the range: 750 - 1676 mm, measuring range ± 700 mm, scale value 1 mm, not separable	X	-	-
	785532:052.26	Measuring bar standard separable Adjusted to track gauge: 1435 mm or to another track gauge in the range: 750 - 1676 mm, measuring range ± 700 mm, scale value 1 mm, separable (2 parts) for a flexible transport	-	X	X
	99.53686	Carrying bag for divisible measuring bars Robust padded fabric bag, two carrying straps, adjustable shoulder strap, dimensions approx 105x28x18 cm	-	X	X
	99.74089	Battery charger UC20 (AAA) Input 100-240 V (AC), incl. 4 diverse plug adapters for worldwide use and 2 pcs. AAA NiMH rechargeable batteries 800 mAh	-	X	X
	99.50968	Laser glasses Improved visibility of the red laser point at daylight, sunlight or light reflections	-	X	X
	785532:100.26	LED lighting device LED lamp with clamp bracket for fixing on the measuring bar I for better visibility of the overhead lines at night or in tunnels	-	X	X

Further measuring bars and equipment



Mechatronik

Picture	Art.-No.	Description
	785532:054.26	Measuring bar narrow gauge Adjusted to track gauge: 1000 mm or to another track gauge in the range: 750 - 1100 mm, measuring range ± 550 mm, scale value 1 mm, not separable
	99.53455	Carrying bag for narrow gauge measuring bar Robust padded fabric bag, two carrying straps, adjustable shoulder strap, dimensions approx 165x28x18 cm
	785532:053.26	Measuring bar universal Flexibly adjustable to track gauges in the range: 750/760/800/950/1000/1067/1100/1200/1435/1445/1450/1458/1520/1524/1600/1668/1676 mm, measuring range ± 700 mm, scale value 1 mm, not separable
	785532:050.26	Measuring bar universal separable Flexibly adjustable to track gauges in the range: 750/760/800/950/1000/1067/1100/1200/1435/1445/1450/1458/1520/1524/1600/1668/1676 mm, measuring range ± 700 mm, scale value 1 mm, separable (2 parts) for a flexible transport
	785532:062.26	Measuring bar standard (inch) Adjusted to track gauge: 4 ft 8.5 in or to another track gauge in the range: 29.53 - 65.98 in, measuring range ± 27.5 in, scale value 1/8 in, not separable
	785532:063.26	Measuring bar standard separable (inch) Adjusted to track gauge: 4 ft 8.5 in or to another track gauge in the range: 29.53 - 65.98 in, measuring range ± 27.5 in, scale value 1/8 in, separable (2 parts)
	785532:061.26	Measuring bar universal separable (inch) Flexibly adjustable to track gauges in the range: 4 ft 8.5 in or to another track gauge in the range: 29.53 - 65.98 in, measuring range ± 27.5 in, scale value 1/8 in, separable (2 parts)